

# SAPF170W technical datasheet

## Protection against job site activities

### THE PRODUCT

THRACE SAPF is a self-adhesive protective fleece suitable for covering and protecting various types of floors and stairs, during intensive construction, renovation, and maintenance projects.

### COMPOSITION

- Base material: Polyester non-woven fleece
- Adhesive: Water-based acrylic
- Top film: Waterproof PE Film 40 µm

### BENEFITS

- Self-adhesive, quick & ready to use
- Provides impact protection
- Impermeable, waterproof
- Easy installation - ideal also for stairs and complex surfaces
- Long-lasting performance
- Easy to remove
- Reusable

### TECHNICAL DATA

Property	Method	Value	
Weight	ISO 9073-1	170	g/m <sup>2</sup>
Thickness	ISO 9073-2	1.2	mm
Strength (MD x CMD)	ISO 9073-3	250 x 210	N/50mm
Elongation (MD x CMD)	ISO 9073-3	50 x 90	%
Standard dimensions		100±1cm x 25±0.5 m	
		100±1cm x 50±0.5 m	

### INSTALLATION & REMARKS:

- Store the product indoors in its original packaging with no direct exposure to sunlight.
- The product is intended for smooth, dry, hard surface only, suitable for floor and stairs. Do not use on wet or damp surfaces, such as freshly laid or stone floors.
- Before application, ensure the surface is clean and dry and underfloor heating is switched off. Always test suitability on a small area before applying.
- Application temperature: between 5°C and 40°C.
- Place only the nonwoven side in direct contact with the surface to assure the anti-slip feature. Press it down and ensure the product is firmly placed on the floor and does not move.
- When using multiple rolls, ensure that there is an overlapping between the rolls of at least 10 cm for better protection of the floor. If necessary, add tape for better fixing.
- For stairs, apply firmly following the shape of the steps, and avoid any wrinkles.
- In case of visible damage to the product, immediately remove and replace. Do not keep the product apply for longer than 3 months.
- After use, gently remove the product. In case of residue, clean them with soft fabric and water.
- In case of reuse, clean the product and store it properly in a dry place.
- Do not re-use damaged pieces.

### NOTES:

Thrace Nonwovens & Geosynthetics S.A. Technical Fabrics reserves the right to alter product specifications at any time without prior notice. The values presented are empirical values based on the current state of production and are subject to customary tolerances, but do not constitute guaranteed properties.

The information contained herein is furnished without charge or obligation and the recipient assumes all the responsibility for its use. Because conditions for use and handling may vary and are beyond our control, Thrace Nonwovens & Geosynthetics S.A. makes no representation about, and is no responsible or liable for, the accuracy or reliability of said information or performance of any product. Any specification, properties or applications listed herein are provided as information only in no way modify, amend, enlarge or create any warranty. Nothing contained herein is to be construed as permission or as any recommendation to infringe any patent.

-  EN ISO 9001:2015
-  EN ISO 14001:2015
-  EN ISO 50001:2018
-  EN ISO 45001:2018

### THRACE NONWOVENS & GEOSYNTHETICS S.A.

Head Office: 20, Marinou Antypa str., 17455, Alimos (Athens), Greece, **T** +30 210 9875044-9 | **F** +30 210 9875040  
 Production Facilities: Magiko Xanthi, 67100, Xanthi, Greece, **T** +30 25410 45675-6 | **F** +30 25410 45658  
[www.thracegroup.com](http://www.thracegroup.com)